



PRINT



SAVE AS PDF

# Sinclair 85W-140 GL-5 Gear Oil

## Sinclair Conventional Gear Oils Industrial Lubricants and Greases

Sinclair 85W-140 GL-5 Gear Oil is formulated specifically for multipurpose, extreme pressure applications, such as conventional differentials, gear boxes, limited slip rear axles, manual transmissions and hypoid gears. Formulated with only the highest quality lubricant oils and our most advanced additive systems that include anti-wear, anti-friction, and extreme pressure agents, along with corrosion and oxidation inhibitors.



### Other benefits include:

- Excellent wear protection, especially under operating conditions of extreme pressure and high torque.
- High thermal breakdown resistance.
- Prevention of, rust, foaming, and corrosion.
- Smoother and quieter operation.

### Robust Anti-Friction, Anti-Wear Chemistry

Sinclair friction and wear control is unsurpassed, with advanced molecules that bond to form a barrier-building shield that reduces friction and wear.

### Stands Up to Even the Most Extreme Conditions

Get outstanding protection even in the most severe hot and cold climates, pressure, micro pitting, or oxidation.

### *Performance You'll Notice*

OEMs are continuing to change driveline designs, and conditions of operations are growing more severe. So you need gear lubricants with outstanding load-carrying capability wherever extreme pressures and shock loading might occur. The technologically advanced driveline gear oils from Sinclair are formulated to meet the challenge of balancing protection, toughness and endurance.

### Performance

**Against load, shear and shock.**

### Strength

**Excellent protection against wear and corrosion.**

### Durability

**Long-lasting thermal stability means longer life for gear, bearings and seals.**

Industry/OEM Specifications

API GL-5	Meets Requirements
Mack GO-J, GO-H, GO-G	Meets Requirements
MT-1	Meets Requirements
SAE J2360, MIL-2105E/F	Meets Requirements
Limited Slip Top Off/Service Fill	Suitable for Use

Typical Properties

Brookfield Viscosity at -12°C, cP	ASTM D2983	55,000
Color	ASTM D1500	8
Flash Point °C	ASTM D92	235
Flash Point °F	ASTM D92	455
Gravity, °API	ASTM D287	25.69
Pour Point °C (°F)	ASTM D5950	-18°C (0°F)
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.9002
Viscosity @ 100°C cSt	ASTM D445	26.39
Viscosity @ 40°C cSt	ASTM D445	347.7
Viscosity Index	ASTM D2270	100

Container/Bulk Availability

5 Gallon	Product Number - 571-008
----------	--------------------------

Available in Bulk

Information accurate as of March 3, 2024